



QDO300 Drying Oven



Quiver QDS5 Carry Oven



Bench Oven, 25Kg



Bench Oven, 45Kg



Flux Oven, 50 & 120Kg

Quality

Reliability

User friendly

Drying Ovens

ESAB's drying & re-drying ovens for Electrodes and SAW flux provides uniform heating thru well dispersed multiple heating elements. Thick glass wool thermal insulation ensures heat retention and efficient utilization of energy.

User friendly controls with simple knobs for portable ovens and digital control panels & display for the bench and flux ovens reduce operator fatigue. The Flux ovens are designed for top loading and bottom dispensing with slag screen that acts as a sieve to filter out contaminants and to protect the heating elements.

Specifications	Quiver QDS5 Carry Oven	QDO300 Drying Oven	Bench Oven 25Kg	Bench Oven 45Kg	Flux Oven 50 Kg	Flux Oven 120 Kg
Input Supply, V/ Ph, HZ	230 / 1, 50	240 / 1, 50	220 / 1, 50	220 / 1, 50	220 / 1, 50	220 / 1, 50
Input Power, W	100	350	400	600	1600	2400
Capacity, Kg	5	5	25	45	50	120
Max Drying Temp, °C	130	300	300	300	400	400
Inner chamber dimensions, mm	73 x 503 (d x h)	70 x 62 x 280	508 x 196 x 196 (l x w x h)	500 x 200 x 220 (l x w x h)	NA	NA
Outer dimensions, mm (l x w x h)	150 x 520	117 x 110 x 547	673 x 330 x 470	610 x 515 x 495	690 x 605 x 995	985x782x1240
Net Weight, Kg	4.80	4.80	24	35.7	69	90
Type of controls	Fixed	Thermostatic (50° C ~ 300° C)	Digital Control	Digital Control	Digital Control	Digital Control